

Package: viewpoly (via r-universe)

July 11, 2026

Title A Shiny App to Visualize Genetic Maps and QTL Analysis in Polyploid Species

Version 1.0.2

Maintainer Cristiane Taniguti <ctaniguti@ufl.edu>

Description Provides a graphical user interface to integrate, visualize and explore results from linkage and quantitative trait loci analysis, together with genomic information for autopolyploid species. The app is meant for interactive use and allows users to optionally upload different sources of information, including gene annotation and alignment files, enabling the exploitation and search for candidate genes in a genome browser. In its current version, 'VIEWpoly' supports inputs from 'MAPpoly', 'polymapR', 'diaQTL', 'QTLpoly', 'polyqtlR', 'GWASpoly', and 'HIDEKAN' packages.

License GPL (>= 3)

Depends R (>= 4.1.0)

Imports shiny (>= 1.6.0), shinyjs, shinyWidgets, config (>= 0.3.1), golem (>= 0.3.1), JBrowseR, dplyr, tidyr, DT, ggplot2, ggpubr, plotly, vroom, abind, reshape2, stats, utils, httr, curl, hidecan, purrr, bs4Dash

URL <https://github.com/Breeding-Insight/viewpoly>

BugReports <https://github.com/Breeding-Insight/viewpoly/issues>

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Suggests testthat (>= 3.0.0), rlang, pkgload, vdiff, markdown, shinytest

Config/testthat/edition 3

Language en-US

Config/pak/sysreqs cmake make libicu-dev libuv1-dev libssl-dev libx11-dev zlib1g-dev

Repository <https://breeding-insight.r-universe.dev>
Date/Publication 2026-07-10 14:15:43 UTC
RemoteUrl <https://github.com/breeding-insight/viewpoly>
RemoteRef HEAD
RemoteSha 97a2625c6d43a2af68154ebe909ab5d404bb7bee

Contents

read_input_hidecan	2
run_app	2

Index	4
--------------	----------

read_input_hidecan	<i>Check hidecan inputs</i>
--------------------	-----------------------------

Description

Check hidecan inputs

Usage

```
read_input_hidecan(input_list, func)
```

Arguments

input_list	shiny input result containing file path
func	hidecan read input function

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

Description

Run the Shiny Application

Usage

```
run_app(  
  onStart = NULL,  
  options = list(),  
  enableBookmarking = NULL,  
  uiPattern = "/",  
  ...  
)
```

Arguments

onStart	A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global .R file can be used for this purpose.
options	Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app.
enableBookmarking	Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app.
uiPattern	A regular expression that will be applied to each GET request to determine whether the ui should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
...	arguments to pass to golem_opts. See <code>'?golem::get_golem_options'</code> for more details.

Index

`enableBookmarking()`, [3](#)

`read_input_hidecan`, [2](#)

`run_app`, [2](#)